

56 Series Granular Fertilizer Applicator

Capacity	6056: 60 cu. ft. (2700lb) 4056: 40 cu. ft. (1800lb)
Outlets	6056: 24 or 30 4056: 16
Application Width	6056: 32-80 ft 4056: 24-60 ft.
Hydraulic Fan Drive	6056: 11.5 gal./min 4056: 11.5 gal./min

1655 Series Granular Fertilizer Applicator

Capacity	33 cu. ft. (900lb)
Outlets	16
Application Width	16-40 ft
Hydraulic Fan Drive	8 gal./min.

Fertilizer Application Specifications

Hopper	Weathertight lid Hopper bottom shut-off slide gates
Metering	<p>Air manifold and venturi system drop for easy cleaning Manual half shut off on either side (except 1655) 28 groove plastic fluted metering rollers OR 12 groove available for more coarse material or higher rates 4056 and 6056 come standard with stainless steel metering</p> <p>HYDRAULIC DRIVE OPTION Hydraulic metering, motor only Hydraulic metering, Rate Control Ready. Includes motor, flow control valve, meter encoder, fan speed and bin level sensors. Does not include ECU, harness or cab display. Hydraulic metering, with granular rate control. Includes motor, ISOBUS compatible ECU* and harness, flow control valve, meter encoder, fan speed and bin level sensors. Does not include display</p> <p>GROUND DRIVE OPTION 60 speed gearbox with 5% between settings In-cab electric clutch control and air manifold monitor Optional hydraulic engage/disengage</p>
Options	12 groove meter roller assemblies for coarse material Outlet blocker kits and line splitters to match a specific number of required runs in special mounting situations Agitator kits Delivery hose quick coupler kits

1.25 inch ID flexible PVC hose

Broadcast deflectors mount individually to the implement frame

Air diffusers for in-row application