

X6 PREMIUM

HIGHLIGHTS

- › Manufactured, Designed, and Engineered by McCormick
- › 4.5 liter BETAPOWER Engine
- › 36 x 12-Speed Gearbox
- › Hydraulic Power Shuttle
- › Push-Button 4WD and Differential Lock
- › 4WD Front Axle
- › Heavy Lifting 3-Point Hitch
- › Deluxe Cab with Completely Flat Foot Deck
- › Digital Front Dash Display
- › 29 gpm (110 lpm) Superior Hydraulic System
- › Instructor's Seat
- › 25 mph (40 kph) Transport Speed
- › Fully locking front and rear differentials
- › Closed Center Hydraulic System
- › 540 and 1000 speed PTO standard equipment



Tractor Model		X6.420	X6.430
Engine			
Rated Engine HP @ 2200 RPM	HP (kW)	111 (82)	121 (89)
Rated PTO HP @ 2200 RPM	HP (kW)	101 (74)	111 (82)
Max. Engine HP @ 1900 RPM with power plus**	HP (kW)	121 (89)	133 (98)
Max. PTO HP @ 1900 RPM with power plus**	HP (kW)	109 (81)	121 (89)
Max. Engine Torque @ 1500 RPM with power plus**	lb ft (Nm)	367 (498)	405 (549)
Engine Type	BETAPOWER diesel engine; Tier 4 using advanced Selective Catalytic Reduction (SCR) technology		
Engine Size	4.5 Liter 4-cylinder		
Fuel / DEF Capacity	gal (liter)	47.6 (180) / 6.6 (25)	
Drive Train			
Standard Transmission	36 x 12 speeds: hydraulic power shuttle; 3-speed power shift; 25 mph (40 kph) transport speed		
Optional Transmission	none	48 x 16 speeds with creeper gear	
Clutch	Wet multi-disc main clutch		
Rear Axle	Internal planetary final drives; heavy duty wet disc brakes; flange axle		
Differential Lock	Front and rear fully locking differentials; electronic control; hydraulic engagement		
4wd Front Axle	Electro-hydraulic engagement with integrated front axle brakes		
Hydraulics, 3-point Hitch, PTO			
Hydraulic System	gpm (lpm)	Closed Center PFC: dedicated steering pump 10 (38), variable implement pump 29 (110)	
Rear Remote Valves	3 spool valves		
Rear 3-point Hitch Type	Category 2; electronic control; rear fender controls		
Rear 3-point Lift Capacity @ Hitch	lb (kg)	11,905 (5,400)	
Rear PTO	540 / 1000 RPM; electro-hydraulic engagement; rear fender controls		
Operator's Area			
Cab	Large 4-post structure; 2 doors; flat foot deck; heavy duty HVAC; premium sound system (suspension available on X6.430)		
Seat and Front Dash	Deluxe air suspended seat; tilt and telescopic steering wheel; instructor's seat		
Wheelbase	in (mm)	100 (2,540)	
Height Over Cab with standard wheel equipment	in (mm)	110.4 (2,805)	
Overall Length with front weights	in (mm)	173 (4,400)	
Base Weight without ballast	lb (kg)	10,360 (4,700)	

*Manufacturer's Calculated Estimates. +/- 5% tolerance.

**PowerPlus is available only when certain operating conditions are met.

