

X6 STANDARD

HIGHLIGHTS

- › Manufactured, Designed, and Engineered by McCormick.
- › 3.6L DEUTZ Engine
- › Versatile Transmission capable of up to 48 speeds
- › Hydraulic Power Shuttle with shuttle modulation control
- › Push-Button 4WD Front Axle
- › Heavy Lifting 3-Point Hitch
- › Large 4-Post Cab with completely flat Foot Deck
- › Open Center Hydraulic System
- › 24.3gpm (92 lpm) Superior Hydraulic System
- › Instructor's Seat standard
- › 25 mph (40 kph) Transport Speed
- › Fully locking front and rear differentials
- › Digital Front Dash Display
- › 540 and 1000 speed PTO standard equipment



Tractor Model		X6.35	X6.45	X6.55
Engine				
Max Engine HP @ 2000 RPM	HP (kW)	110 (81)	119 (88)	126 (93)
Max PTO HP @ 2000 RPM	HP (kW)	86 (64)	95 (71)	102 (76)
Max. Engine Torque @ 1500 RPM	lb ft (Nm)	324 (440)	351 (476)	368 (500)
Engine Type	DEUTZ® liquid cooled diesel engine; Tier 4 using advanced Selective Catalytic Reduction (SCR) technology			
Engine Size	3.6 Liter, 4-cylinder			
Fuel / DEF Capacity	gal (liter)	39 (150) / 5 (20)		
Drive Train				
Standard Transmission	12 x 12 speeds; hydraulic power shuttle			
Optional Transmission (1)	36 x 12 speeds; hydraulic power shuttle, 3-speed power-shift			
Optional Transmission (2)	48 x 16 speeds; hydraulic power shuttle, 3-speed power-shift, creeper gear			
Brakes	Heavy duty wet multi-disc brakes			
Differential Lock	Limited slip			
4wd Front Axle	Electro-hydraulic engagement with integrated front axle brakes			
Hydraulics, 3-point Hitch, PTO				
Hydraulic System	gpm (lpm)	Open center system; 16.4 (62) dedicated implement pump + 7.9 (30) dedicated steering pump		
Rear Remote Valves	3 Valves			
Standard Rear 3-point Hitch Type	Category 2 with telescopic ball ends; electronic lift control			
Optional Rear 3-point Hitch Type	Category 2 with quick attach hooks; electronic lift control			
Rear 3-point Lift Capacity	lb (kg)	13,227 (6,000) standard		
Rear PTO	2 Speeds (540/1000 rpm) standard; Optional 4 speeds (540/540E/1000/1000E); Groundspeed PTO optional			
Operator's Area				
Cab	Deluxe 4 post cab, flat foot deck, radio system, silent-block suspension, instructor's seat			
Seat and Front Dash	Deluxe air suspended seat; tilt and telescopic steering wheel			
Wheelbase	in (mm)	95 (2,420)		
Height Over Cab	in (mm)	104 (2,650)		
Base Weight without ballast	lb (kg)	10,361 (4,700)		

*Manufacturer's calculated estimates. +/- 5% tolerance.

--	--	--