

## I-2200 Specifications

<b>Operating Depth Range</b>	0 inches - 5inches					
<b>Operating Speed (mph)</b>	8-12 mph					
<b>Blade Mount</b>	Coil-Tech Coulter II: 1 5/8 inch diameter coil					
<b>Blade Type</b>	22 inches x 5mm - 8 wave (2 1/2 inch deep wave) - 13 wave ( 1 3/4 inch deep wave)					
<b>Blade Spacing</b>	5 inch					
<b>Vertical Travel</b>	5 inches					
Size	Frame Sections	Number of Coulters*	Transport Height	Transport Width	Approx. lbs with harrows	H.P. Required*
16'	3	37	10'	10"	14,00	200 - 240
20'	3	49	11'2"	13'3"	17,000	240 - 300
24'	3	57	12'8"	15'3"	19,100	290 - 360
28'	3	69	13'	15'8"	23,700	340 - 420
31'	3	73	14'6"	21'	24,400	380 - 470
36'	3	85	14'2"	21'	30,000	440 - 540
41'	3	97	16'6"	19'	36,800	500 +
41'	5 Bi-fold	97	13'6"	18'9"	32,300	500 +
50'	5 Bi-fold	119	14'3"	19'	47,170	500+

\* Horsepower requirements vary by speed and operating depth. Transport dimensions include harrows.

\*\* Number of coulters varies, depending on spacing of shank kit.

## SwitchBlade 1,300lb Hyd. Shank Kits

Size	15" Spacing # of Shanks	15" Spacing Fertilizer Coverage	30" Spacing # of Shanks	30" Spacing Fertilizer Coverage
16'	11	13'9"	6	15'
20'	15	16'3"	8	17'6"
24'	17	21'3"	9	22'6"
28'	21	26'3"	11	27'6"
31'	23	28'9"	12	30'
36'	27	33'9"	14	35'
41'	31	38'9"	16	40'

41' **	31	38'9"	16	40'
50' **	39	48'9"	19'	47'6"

Shank kits require an additional average of 3 horsepower per shank.

\*\* 5 Section bi-fold frame

### Operating Guide

Operation	Crop Type	Depth
Seed bed preparation	Corn, Cereal Grains, Hay & Pasture	1.5" - 2" (less than or equal to planting depth)
Seed bed preparation	Soybean, Edible beans, Canola, Pulse Crops	2" - 3" (equal to or slightly more than planting depth)
Fall residue management	All crops	2.5" or deeper (coulters must stay clear of field surface)
Seeding	Cereals, canola, cover crops, hay/pasture blend	2" or less
Fertilizer Application	All types	2" or more