

## 245 & 246 Pull-Type Specifications

<b>Hopper</b>	<b>245:</b> 40 cubic feet Mild steel with 2 component primer and 2 component urethane top coat paint <b>246:</b> 60 cubic feet Polyurethane tank Weathertight lid Product level sight gauge Hopper bottom shut-off gates
<b>Booms</b>	<b>245:</b> 50 foot spread, breakaway tips <b>246:</b> 60 foot spread, breakaway tips Self-leveling Manual fold
<b>Metering</b>	Ground driven <b>245:</b> Half shut-off on either side <b>246:</b> 4 section shut-off <b>245:</b> 28 groove plastic fluted metering roller – 12 groove available for more coarse material or higher rates <b>246:</b> Stainless steel metering In-cab electric clutch control and air manifold monitor 60 speed gearbox with 5% between settings Air manifold and Venturi system drop for
<b>Chassis</b>	<b>245:</b> 6000 lb rubber torsion axle <b>245:</b> 12.5 L – 15 inch tires <b>246:</b> 7000 lb rubber torsion axle <b>246:</b> 31 X 13.5 - 15 inch tires 6 bolt hubs
<b>Fan</b>	Hydraulic drive:10.5 GPM - hydraulic lines to hitch included 245/246: 9 HP gas engine fan drive 18 inch impeller
<b>Options</b>	12 groove roller assemblies for coarse material Agitator kit <b>245:</b> Stainless steel metering <b>246:</b> Stainless steel metering is standard
<b>Dimensions</b>	Height: 6 ft. 8 in. Width: 7 ft. 8 in. Length: 18 ft. <b>245:</b> Weight: 2250 lb. <b>246:</b> Weight: 3100 lb.

