

X1



Tractor Model		X1.25H	X1.35	X1.35H	X1.37C	X1.37HC	X1.45	X1.45C	X1.45HC	X1.55H	X1.55C	X1.55HC						
Rated Engine Power	HP (kW)	24 (18)	35 (26)	35 (26)	37 (27.1)	37 (27.1)	47 (35)	47 (35)	47 (35)	55 (41)	55 (41)	55 (41)						
Rated Engine Speed		2600 RPM						2600 RPM										
Rated PTO Power	HP (kW)	18 (13)	29 (21)	29 (21)	33 (24.2)	32 (23.5)	42 (31)	42 (31)	42 (31)	47 (35)	47 (35)	47 (35)						
Engine Type		3-cylinder diesel		3-cylinder diesel		4-cylinder diesel		4-cylinder diesel										
Displacement		1.2 liter (73 in ³)		1.7 Liter (104 in ³)		2.01 Liter (127.1 in ³)		2.3 Liter (140 in ³)										
Aspiration		Natural						Natural			Turbocharged							
Emissions System		EPA Tier 4		Tier 4, using combined DOC + DPF				Tier 4, using combined DOC + DPF										
Fuel Capacity	gal (liters)	6.2 (23.6)	9.3 (35), tank under platform			12 (45), ground level tank			9.3 (35), tank under platform									
Transmission Type		Hydrostatic	Mechanical	Hydrostatic	Mechanical	Hydrostatic	Mechanical		Hydrostatic	Hydrostatic	Mechanical	Hydrostatic						
Main Clutch		Dry single disc		None	Dry single disc	None	Dry single disc		None	None	Dry single disc	None						
Speeds		2-range HST		12F x 12R	3-range HST		12F x 12R	3-Range HST		12F x 12R	3-range HST							
Shuttle Type		2 Foot pedals		Synchronized	2 Foot pedals		Synchronized	2 Foot pedals		Synchronized	2 Foot pedals							
Differential Lock		Mechanical, heel pedal						Mechanical, heel pedal										
Rear Brakes		Wet disc brakes with R and L pedals		Wet disc brakes with suspended R and L pedals														
Front Axle Type		4wd with mechanical engagement		4wd with mechanical engagement, 62-degree steering angle														
Rear PTO Type		540 RPM, live transmission driven		Independent, electronically engaged, 540 and 540e standard														
Mid PTO		Standard, 2500 RPM		Not available														
Hydraulic System		Open center system						Open center system										
Hyd. Flow at Remotes	gpm (lpm)	4.8 (18.2)	8.9 (34)			11.1 (42)	10.4 (39.4)		11.1 (42)			11.1 (42)						
Loader Joystick		Mounted to loader sub frame		Standard with 2 mid-mount valves														
Rear Remote Valves		1 optional		2 standard														
3-pt Type		Category I		Category I with telescopic stabilizers and lower links														
3-pt Lift Capacity	lb (kg)	1,500 lbs (680) at ball ends		3,306 (1500) at ball ends; 2,425 (1100) at 24"														
Operator's Area		Folding ROPS, right and left entry, rubber foot deck cover				Cab with HVAC, 2 doors, flat foot deck			Open Station ROPS	Cab with HVAC, 2 doors, flat foot deck		Open Station ROPS	Cab with HVAC, 2 doors, flat foot deck					
Seat and Steering		Vinyl seat, hydrostatic steering		Adjustable vinyl seat, tilt steering wheel, hydrostatic steering, 56 degree steering angle														
Wheelbase	in (mm)	60 (1530)		70.9 (1800)			71.1 (1,806)			70.9 (1800)								
Height over ROPS/Cab	in (mm)	88 (2240)		94 (2390)	94 (2390)	96.8 (2,460)		96 (2440)	97 (2460)	97 (2460)	96 (2440)	97 (2460)	97 (2460)					
Base Weight	lb (kg)	1,810 (821)		4,053 (1840)		4,053 (1840)		4,211 (1,910)		4,195 (1,903)		4,118 (1870)	4,442 (2015)		4,442 (2015)		4,453 (2020)	