

# X4



Tractor Model		X4.20	X4.30	X4.40	X4.50
<b>Performance</b>					
Max. ISO Engine HP @ 1900 RPM	HP (kW)	64 (47)	72 (53)	79 (58)	88 (65)
Max. ISO PTO HP @ 1900 RPM*	HP (kW)	54 (40)	61 (45)	68 (50)	72 (53)
Max. Engine Torque @ 1600 RPM	lb ft (Nm)	180 (244)	200 (271)	221 (300)	278 (378)
<b>Engine</b>					
Engine Type	DEUTZ® liquid cooled diesel engine; Tier 4 compliant using <i>only</i> cooled EGR + DOC system ( <i>no regeneration</i> )				
Engine Size	2.9 Liter, 4-cylinder				
Fuel Capacity	gal (liter)	20 (75)			
<b>Drive Train</b>					
Transmission Type	12 x 12 speeds; 4 gears and 3 ranges; synchronized mechanical shuttle with left hand shuttle lever, 25mph (40kph)				
Optional Transmission	16 x 16 speeds with creeper gear; synchronized mechanical shuttle with left hand lever, 25mph (40kph)				
Rear Axle	Heavy duty flange rear axle; internal planetary final drives; wet disc brakes				
Differential Lock	Fully locking rear differential; mechanical engagement via foot pedal				
4wd Front Axle	Push button 4wd engagement; outboard planetary final drives; automatic 4-wheel braking				
Tire Type	Radial tires standard				
<b>Hydraulics, 3-point Hitch, PTO</b>					
Hydraulic System/Max. Flow	gpm (lpm)	Open center system with separate steering and implement pumps			
Hydraulic Flow Rate	gpm (lpm)	Dedicated steering pump 5.3 (20); Dedicated implement pump 11.9 (45)			
Rear Remote Valves	1 standard, 2 optional; with ISO 1/2" quick couplers				
Rear 3-point Hitch Type	Category 2; mechanical operation; position and draft sensing				
3-point Lift Capacity @ Hitch	lb (kg)	5,952 (2,700)			
Rear PTO	540 RPM standard; 540/1000 RPM optional; mechanical engagement				
<b>Operator's Area</b>					
Operator's Area	Cab or 2-post folding ROPS				
Seat and Front Dash	ROPS: Adjustable vinyl seat, mechanical suspension; tilt steering wheel Cab: Cloth seat, air suspension; tilt and telescopic steering wheel				
Wheelbase	in (mm)	85.2 (2,164)			
Height Over ROPS in Raised Position	in (mm)	98.4 (2,500)			
Height Over Cab	in (mm)	98.5 (2,502)			
Overall Length without Front Weights	in (mm)	155 (3,930)			
Base Weight without Ballast	lb (kg)	ROPS: 6,724 (3,050) Cab: 7,275 (3,300)			

\* Manufacturer's calculated estimate. +/- 5% tolerance.

--	--	--	--