

**Strip Till Granular Fertilizer Applicator Specifications**

	<i><b>ST-6</b></i>
<b>Hopper Capacity</b>	185 cu ft 6 Tons
<b>Tank Configuration</b>	Single compartment
<b>Tank Material</b>	High Density Polyethylene
<b>Metering Sections</b>	Up to four sections (Electric clutches per section)
<b>Tank Features</b>	Air Manifold gauge Hopper Screen Ladder and platform assembly
<b>Air Manifold</b>	8, 12, 16, 18, 20 and 24 Outlet manifolds (choose at the time of ordering)
<b>Meter</b>	Plastic peg meters rollers with brush for self cleaning Manual hopper bottom shut-off slide gates PWM Valve Meter encoder, Fan speed sensor, Bin level sensor Low rate rollers available
<b>Implement Mounting</b>	Skid mounting available - contact dealer *ST-10 does not come standard with mounting hardware.
<b>Fan</b>	Hydraulic fan drive Second fan option for high rates, swaths, or ground speeds Second fan standard on 24 row models
<b>Optional Control Packages and Scales</b>	ISOBUS Controls* (includes ECU and harness) Digi-Star Scale Kit (includes one cab display) or available as ISOBUS
<b>Hydraulic Requirements</b>	Requires 30-42 gpm @ 2800 psi (single fan or dual fan) Case drain required Hoses to tractor not included

\*For use with 3rd party ISOBUS cab consoles utilizing prescription mapping (i.e. John Deere 2630™, Case IH Pro 700™, etc.)\* ISOBUS compliance does not guarantee compatibility with all functionality on 3rd party ISOBUS displays; Non-ISOBUS displays are not compatible with this controller. Always consult with the display manufacturer before purchase - Prescription mapping and/or auto section control may require software unlock. Ensure latest display firmware version is installed.